

# BIO-SOL SEPTITANK

## BST

**Maintains septic tanks and small effluent treatment works. Prevents blockages and eliminates foul odours. Reduces frequency of dredging.**

### Action

Bio-Sol Septitank contains micro-organisms specially selected for their ability to degrade grease, cellulose and animal waste. Septic tanks and cesspits degrade and mineralise waste organic matter. Part of the waste they receive, e.g. grease and paper, is difficult to degrade. It accumulates and reduces the effectiveness of the tank. Efficient biological action also encourages the degradation and the remediation of the sludge that accumulates in the bottom of the tank.

### Application

Pour 25g per 4 people using system into toilet bowl or suitable inlet and flush. Use once per week.

### Composition

Bio-Sol Septitank is a compound of nutrient, starter enzymes and selected strains of microorganisms able to degrade fats, organic waste, organo sulphur compounds and cellulose.

### Safety

The micro-organisms in Bio-Sol Septitank conform to EC EFB Class1. This class contains micro-organisms which have never been described as causal agents in human illness and which pose no threat to the environment.

### Notes

Store away from heat and humidity.  
Keep out of the reach of children.  
The bacteria and fungi in Bio-Sol Septitank are protected from bleaches and disinfectants. To get the best results from your septic tank or waste treatment system you should minimise the use of biocides.  
SOLTECH provides a complete biological surface and drain-cleaning package which replaces toxic chemicals and maintains clean hygienic surfaces and clear odour free drains.

- Packaging 1Kg, 5kg.